


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification</b> <sup>6</sup> : <b>B05B 11/00, 7/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/13585</b> <b>(43) International Publication Date:</b> 17 April 1997 (17.04.97)
<b>(21) International Application Number:</b> PCT/NL96/00378 <b>(22) International Filing Date:</b> 30 September 1996 (30.09.96) <b>(30) Priority Data:</b> 1001366 6 October 1995 (06.10.95) NL <b>(71) Applicant (for all designated States except US):</b> PARK TOWERS INTERNATIONAL B.V. [NL/NL]; Zuiderkade 31, NL-1948 NG Beverwijk (NL). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> VAN DER HEUDEN, Edgar, Ivo, Maria [NL/NL]; Joh. Huizingastraet 14, NL-1827 NA Alkmaar (NL). <b>(74) Agent:</b> BAKKUM, R., J.; Van Exter Polak & Charlouis B.V., P.O. Box 3241, NL-2280 GE Rijswijk (NL).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** DEVICE FOR DISPENSING AN AIR-LIQUID MIXTURE, IN PARTICULAR FOAM, AND OPERATING UNIT INTENDED THEREFOR**(57) Abstract**

Device for dispensing an air-liquid mixture, such as foam, comprising a liquid container and an operating unit (1), which unit comprises at least a concentric air pump (2) and liquid pump (3), which each comprise a piston chamber (4, 9) with a piston (5, 10) which is displaceable therein and an inlet and discharge, and operating component (11) for operating the two pumps (2, 3), which component is integral with the liquid piston (10) and comprises an outflow channel (15) with a dispensing opening, while shut-off means, which make it possible to suck up air or liquid, respectively, and dispense them, are present in the inlet and discharge of the pumps (2, 3), the air pump (2) comprising a double-acting shut-off device which can be operated actively by the operating component (11) and shuts off both the inlet of air to the air pump (2) and shuts off the discharge of air therefrom, and the air piston (5) is an air piston (5) which can be moved freely at least over a small distance with respect to the operating component (11).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

Short title: Device for dispensing an air-liquid mixture,  
in particular foam, and operating unit  
intended therefor.

The present invention firstly relates to a device  
for dispensing an air-liquid mixture, in particular a foam,  
at least comprising a liquid container and an operating  
unit, which unit comprises at least an air pump and a  
5 liquid pump, which are essentially concentric, and each  
comprise a piston chamber with a piston which is dis-  
placeable therein, while each pump comprises an inlet and a  
discharge, and an operating component is present for  
operating the two pumps, which operating component is  
10 integral with the piston of the liquid pump, and therein  
comprises an outflow channel with a dispensing opening,  
which channel can be connected to the discharge of the  
pumps, while shut-off means, which make it possible to suck  
up air or liquid, respectively, into the appropriate piston  
15 chambers and to dispense these fluids to the outflow  
channel, are present in the inlet and discharge of the air  
and liquid pump, the connection between the outflow channel  
and the relevant pumps being interrupted while air or  
liquid is being sucked up, and the air pump comprises a  
20 double-acting shut-off device, which shuts off both the  
inlet of air to the air pump and shuts off the discharge of  
air therefrom.

A device of this kind is disclosed by EP-A-  
0 613 728 and is designed to dispense foam. To this end,  
25 foam-forming means are present in the outflow channel.  
Moreover, a mixing chamber is in this case present which  
can be connected to the discharges of the air and liquid  
pumps and the outflow channel.

The double-acting shut-off device for the air pump  
30 comprises a resilient shut-off component, comprising a  
cylindrical wall section, an annular outer section which  
extends outwards from the said cylindrical wall section and  
an annular inner section which extends inwards from the  
said wall section. The resilient shut-off component is

fastened with the said cylindrical wall section to the inner wall of the air piston.

However, the action of the abovementioned foam-dispensing device is not optimal, since problems may occur during dispensing. Dispensing can be impeded by the double-acting shut-off device sticking to other components of the device. If, during use, a section which has stuck fast suddenly comes loose, uncontrolled pressure differences may occur, which have undesirable consequences. Consequently, a relatively large amount of gas or liquid may suddenly emerge. In both cases, this may lead to contamination and spattering, and therefore to foam being formed incorrectly or not at all. The liquids to be dispensed are often substances which are irritating to the eyes. It will be clear that this uncontrolled dispensing should be avoided. Any sticking of the shut-off device likewise leads to problems with refilling the air piston chamber with air after use.

In addition, the said shut-off device is a so-called passive shut-off device, which is opened by pressure differences generated in the unit. In other words, the shut-off device comprises a combination of two non-return valves. The relevant annular sections of the said shut-off device shut off the inlet and discharge, respectively, of the air piston chamber under a certain prestressing. When the pressure drops or rises suitably, the inlet and discharge, respectively, are connected to the air piston chamber.

The present invention aims to provide a device of the type mentioned in the introduction which does not have the problems of the prior art device and furthermore has a generally improved action. To this end, the invention has the characteristic that the double-acting shut-off device for the air pump is a shut-off device which can be operated actively by the operating component, and in that the air piston is an air piston which can move freely at least over a short distance with respect to the operating component.

In this way, any problems with sticking and the

like are completely eliminated. Dispensing can be carried out in a very controlled manner, since the inlet or discharge, respectively, is opened or closed, respectively, directly at the instant that the operating component is  
5 operated. Sudden pressure changes in the outflow channel resulting from the shut-off device sticking therefore do not occur. If any sticking does occur, this sticking is eliminated not by a pressure increase but by a mechanical action. All this will be explained in further detail below  
10 in the description of the figures.

The device according to the invention is not limited to dispensing foam, but can likewise be used for dispensing an atomizing liquid. This is achieved by suitable configuration of the outflow channel, whether  
15 using a mixing chamber, foam-forming component, etc., or not.

In the rest of the description, however, the device according to the invention will be discussed exclusively with reference to dispensing foam.

20 In the following description, liquid is intended to mean any flowable material, ranging from water, thin liquids, through to pastes, including suspensions, etc.

Preferably, the double-acting shut-off device is designed in the form of a sealing ring forming part of the  
25 operating component, and the piston of the air pump is designed in the form of an annular piston, which is freely movable with respect to the other components, while the operating component additionally comprises a driver, which is situated upstream of the sealing ring, viewed in the  
30 intended outflow direction of the air, an inner rim of the annular piston is situated between the sealing ring and the driver, and the driver, along its circumferential edge which can interact with the annular piston, comprises recesses, the sealing ring and the driver being able to  
35 interact with one another in a sealing manner in the at-rest position of the operating unit, and the distance in this case between the sealing ring and the driver being larger, at the location of the inner rim of the annular piston, than the thickness of the inner rim of the annular

piston, and a connection to the outflow channel can be achieved between the sealing ring and the driver.

In this manner, an actively operable air admission or discharge valve for the air piston chamber is provided, the action of which will be explained in more detail below in the description of the figures.

Advantageously, the opening in the freely movable annular piston is as small as possible, in order to avoid the said piston being pulled out of position (tilted) with respect to the operating component.

In this embodiment of the device according to the invention, the annular piston is freely movable over a small distance, since the latter is driven by the sealing ring when the device is used during dispensing of foam, while the annular piston is returned to the starting position by the driver after use, during the returning movement of the operating unit.

Preferably, an additional driver is situated past the sealing ring, viewed in the intended outflow direction of the air, so that the sealing ring can be clamped between the said driver and the annular piston during dispensing of foam, in order to improve the sealing of the air inlet.

In another advantageous embodiment of the device according to the present invention, the double-acting shut-off device forms a component of the piston of the air pump, the piston of the air pump is designed in the form of an annular piston, which is freely movable with respect to the other components, while the operating component comprises two drivers, between which the annular piston is situated, the first driver, which is situated downstream of the annular piston, viewed in the intended outflow direction, having a larger radial dimension than the other, second driver, one or more air inlet openings are present in the annular piston, which openings are situated between the outer circumference of the first and the second drivers, viewed in the radial direction, and a connection to the outflow channel can be achieved between the drivers.

This embodiment likewise provides an actively operable double-acting shut-off device.

Advantageously, the annular piston comprises two axial, circumferential thickened portions, which are located radially at a distance from one another and extend in opposite directions, a first thickened portion which  
5 extends in the intended outflow direction and can interact with the first driver, and a second thickened portion which extends in the opposite direction and can interact with the second driver, the first thickened portion lying further towards the outside, in the radial direction, than the  
10 second. It will be clear that the thickened portions may be present, in addition to on the annular piston, also on the relevant drivers, with a corresponding action.

The air piston is preferably manufactured from a resilient material.

15 In order to improve the positioning of the annular piston, the latter is advantageously connected at least locally to the operating component. However, it should be noted here that it is essential in the device according to the invention that the air piston be freely movable at  
20 least over a small distance with respect to the operating component.

In particular, in the device according to the invention a mixing chamber is present for mixing air and liquid, which chamber is connected to the outflow channel,  
25 the discharge of the air pump and the discharge of the liquid pump. Preferably, one or more foam-forming components are present in the outflow channel. In this way, the device according to the invention can be made suitable both for dispensing atomizing air-liquid mixtures as well  
30 as for dispensing foam.

In a particularly preferred embodiment of the device according to the invention, the liquid piston is a cylindrical component with an inlet side and a discharge side, which component is open on two sides and on the  
35 discharge side comprises a seat, with which a sealing element extending into the liquid chamber can interact, and additionally that section of the sealing element which extends into the chamber can interact slidingly with friction with an additional cylindrical component in the

liquid piston chamber in order to force the sealing element into the seat during filling of the piston chamber and to force it out of the seat during emptying of the chamber.

Particularly advantageously, the shut-off device in  
5 the inlet of the liquid pump is designed in the form of a stopper, which can move freely between two stops in the liquid piston chamber and can interact with a seat in the liquid inlet, which stopper moreover forms the additional cylindrical component.

10 Thus, according to the invention this shut-off device is likewise designed as an active shut-off device, in contrast to the conventional shut-off devices in accordance with the prior art, which are generally formed by a pressure-sensitive non-return valve, such as a ball or the  
15 like in a seat, which can be removed from the seat by a pressure difference. The known sticking phenomena which were discussed in the introduction can of course also occur in these non-return valves in accordance with the prior art.

20 Furthermore, the invention provides an operating unit which is evidently intended to be used in a device according to the invention.

Finally, a piston is provided which is intended for an air pump for an operating unit according to the  
25 invention.

The invention will be explained in more detail below, with reference to the appended drawing, in which:

- Fig. 1 shows a first embodiment of an operating unit according to the invention during the dispensing of  
30 foam;  
Fig. 2 shows the operating unit according to Fig. 1, but after dispensing, during the return movement;  
Fig. 3 shows a second embodiment of the operating unit according to the invention during dispensing;  
35 Fig. 4 shows the operating unit according to Fig. 3 after dispensing, during the return movement; and  
Fig. 5 shows an enlargement of the shut-off device of the discharge of the liquid pump in the operating unit



according to the invention in the two operating positions.

In Fig. 1, a first embodiment of an operating unit according to the invention is indicated diagrammatically by  
5 1. This operating unit 1 comprises an air pump 2 and a liquid pump 3.

The air pump 2 comprises a piston chamber 4 and an annular air piston 5, which piston 5 is in contact via the ring 6 with an inner wall 7 of the piston chamber 4, and  
10 additionally has an annular flat section 8.

The liquid pump 3 comprises a liquid piston chamber 9 with a liquid piston 10. The liquid piston 10 is an essentially cylindrical component which is open on two sides.

15 The said liquid pump piston 10 is integral with an operating component 11 and is received, with the interposition of suitable ribs 12 and 13, in a recess 14 in the operating component 11. It will be clear that the said ribs 12 and 13, respectively, may be present either on the  
20 outside of the end of the piston 10 or also on the inside of the recess 14. The operating component 11 comprises an outflow channel 15 and a dispensing opening 16. The location where the operating component can be operated with the aid of a finger is indicated by 17.

25 The end of the liquid piston, which is provided with ribs 12 and 13, respectively, and is denoted by reference numeral 18, comprises an opening 22, and forms a seat 19 for a sealing element 20 which extends into the piston chamber 9. The said sealing element 20 can seal the  
30 opening 22 in the end 18 by means of a sealing section 21. The sealing element 20 extends on the other side into a stopper 23, which consists of a cylindrical component which is closed on one side and is provided with projections 24, which can move between a shoulder 25 and a stop 26. The  
35 closed end of the stopper 23 is denoted by 27. The stopper 23 can seal the inlet opening 45.

The sealing element 20 comprises a number of lips 29 distributed over its circumference at one end 28, in

order to assist the engagement between the said element and the component 23 and to increase the frictional resistance.

30 denotes a spring which rests against the stop 26 and is used as a restoring means for the operating  
5 component 11.

31 denotes a cover part with a sealing ring 32 and an internal screw thread 33, by means of which the operating unit can be screwed onto an opening in a liquid container.

10 34 denotes an diptube, the length of which is generally such that it extends to near the bottom of the liquid container.

35 denotes a mixing chamber which is provided on the inside with baffles 36, against which the end 21 of the  
15 sealing element 20 can be supported without sealing. 37 and 38 denote foam-forming components made of screen material. This screen material can expediently be chosen from, for example, porous materials, sintered materials, wire gauze screens, etc.

20 The double-acting shut-off device is formed by the assembly of the annular piston 5, a sealing ring 39 which is fastened to the operating component 11, a driver 40 with a circumferential thickened portion 41 and projections 42, and a driver 43 of the operating component 11. The said  
25 shut-off assembly is depicted in more detail in the enlargement A of Fig. 1.

Fig. 1 shows the embodiment during the downward stroke of the operating component 11, liquid being moved by the piston 10 out of the liquid chamber 9, between the  
30 section 21 of the sealing component 20 and the seat 22 of the end 18 of the piston chamber and being conveyed to the mixing chamber 35. Air is conveyed, between the sealing ring 39 and the channels formed by the ribs 12 and 13, respectively, and the inner wall of the recess 14, to the  
35 mixing chamber 35 by the piston 5. The liquid is struck by a plurality of air flows essentially transversely to the direction of flow. The liquid thus enters the mixing chamber 35 in the form of a cylindrical flow of liquid, as a result of which an outstanding mixing is obtained.

After the air-liquid mixture has passed the foam-forming components 37 and 38 in the outflow channel 15, a foam is dispensed at 16. During the downwards movement of the operating component 11, the spring 30 is compressed and will return to its initial position when the operating component is released.

Furthermore, during the said downward movement of the piston 5, the sealing ring 39 will be pressed against the shoulder 43 as a result of friction between the piston section 6 and the wall 7 of the air pump 2, as a result of which a connection is achieved, between the driver 40 and the sealing ring, with the channel formed by the ribs 12 of the liquid piston 10 and the inner wall of the recess 14 in the operating component, and air can thus flow to the mixing chamber.

Moreover, during the downward movement the sealing element 20 is removed from the seat 22 by interaction between the inner wall of the component 23 and the lips 29 at the end of the said sealing element 20. In this case, the component 23 seals off the connection to the container, via the diptube, and the end 44 of the component 23 is then located in the seat of the opening 45 of the liquid piston chamber inlet. During this movement, the end 21 of the sealing element 20 bears against the baffles 36 in the mixing chamber 35.

Fig. 2 shows the operating unit according to Fig. 1 in a position after foam has been dispensed, during the return movement of the operating component 11. During this movement, the annular piston 5 is to a certain extent held back by friction between the section 6 and the wall 7 of the air pump 2, but is driven by the driver 40 or the small projections 42 thereof. During this movement, the annular thickened portion 41 presses the sealing ring 39 from the rim 8 of the annular piston 5, as a result of which the piston chamber 4 is connected to ambient air which can flow in via the passage 47 between the operating component 11 and the fastening cap 31, while the connection with the outflow channel 15 is interrupted. In this position, the distance between the sealing ring 39 and the driver 40 at

the location of the inner rim 8 of the annular piston 5 is greater than the thickness of the said inner rim 8, in order to permit sealing between the sealing ring 39 and the driver 40 as well as to enable air to be let into the air  
5 piston chamber 4.

During the return movement of the operating component 11, the component 23 is also removed from the seat 45, and in the process the lugs 24 come to bear against the stop 26, it being possible for the liquid to be  
10 drawn out of the container, via the diptube, into the liquid piston chamber 9 by the piston 10. During this movement, the section 21 of the sealing element 20 seals the opening 22 by interacting with the seat 19.

A channel 46 is present in the air pump 2, in order  
15 to be able to smooth out the pressure changes in the container which arise as a result of liquid being removed therefrom.

It should be pointed out that in the position of rest of the operating unit 1 according to the invention,  
20 the discharge of the air pump 2 is closed by the interaction between the sealing ring 39 and the driver 40. As a result, any liquid residues flowing back after use cannot reach the air piston chamber 4.

Fig. 3 shows a second embodiment of an operating  
25 unit according to the invention which is substantially identical to that of Fig. 1 and 2, the same reference numerals being used for corresponding components. The double-acting shut-off device in this figure is, however, designed differently. The shut-off device is in this case  
30 not formed by a separate sealing ring, but here forms a component of the annular piston 5.

The annular piston 5 comprises a cylindrical section 52, which in this case is fastened to the operating component 11 between the lugs 12 and the recess 14 and can  
35 move flexibly over some distance with respect to the operating component 11.

It will be clear that this fastening is not, however, necessary, and the annular piston 5 can likewise be used as a separate, loose component in this embodiment.

- 11 -

A section 55 of the annular piston 5 is provided with circumferential thickened portions 53 and 54, between which air inlet openings 52 are situated. The thickened portions 53 and 54 can interact with drivers 50 and 51, respectively, which are respectively present on the operating component 11 and the liquid piston 10. The driver 50 has a larger radial dimension than the driver 51.

In the downward stroke, during the dispensing of foam, the operating unit 11 is situated in the position in accordance with Fig. 3, it being possible for air to move through, between the driver 51 and the thickened portion 54 on the piston section 55, to the channels which are formed by the ribs 12, 13 and the inner wall 14 of the operating component 11.

After dispensing, the operating component 11 will be moved back by the spring 30 to the initial position and will then assume the position in accordance with Fig. 4. In this position, air can flow via the intermediate space 47, between the driver 50 and the annular thickened portion 53, and through the inlet openings 52 into the air piston chamber 4.

Finally, Fig. 5 shows an enlargement of a particular embodiment of the sealing section 21 of the sealing element 20, in the top version during dispensing of liquid from the liquid piston chamber 9 and in the bottom version during filling of the liquid piston chamber 9. The sealing section 21 comprises a number of positioning lugs 56, preferably four, which are distributed over the circumference. Correct positioning of the sealing element 20 and its sealing section 21 with respect to the opening 22 provides a symmetrical cylindrical outflow of liquid which greatly benefits the quality of the foam which is eventually formed. This is particularly important in the case of relatively viscous liquids.

It will be clear that although a circumferential lug is present on the driver in Figs 1 and 2, this driver can likewise be of flat design, and a circumferential thickened portion can be arranged on the sealing ring. The same applies to the embodiment in accordance with Figs 3

and 4, likewise it being possible for a circumferential thickened portion to be arranged on the relevant drivers instead of thickened portions on the piston. A similar action is thus obtained.

- 5           Sticking of shut-off devices or the like no longer plays any role in the operating unit according to the invention, since the double-acting shut-off device is operated actively by the operating component and is opened and closed, respectively, irrespective of pressure  
10 differences occurring.

## CLAIMS

1. Device for dispensing an air-liquid mixture, in particular a foam, at least comprising a liquid container and an operating unit (1), which unit (1) comprises at least an air pump (2) and a liquid pump (3), which are  
5 essentially concentric, and each comprise a piston chamber (4, 9) with a piston (5, 10) which is displaceable therein, while each pump comprises an inlet and a discharge, and an operating component (11) is present for operating the two pumps, which operating component (11) is integral with the  
10 piston (10) of the liquid pump (3), and therein comprises an outflow channel (15) with a dispensing opening (16), which channel (15) can be connected to the discharge of the pumps, while shut-off means, which make it possible to suck up air or liquid, respectively, into the appropriate piston  
15 chambers and to dispense these fluids to the outflow channel (15), are present in the inlet and discharge of the air (2) and liquid pump (3), the connection between the outflow channel (15) and the relevant pumps being interrupted while air or liquid is being sucked up, and the  
20 air pump (2) comprises a double-acting shut-off device, which shuts off both the inlet of air to the air pump (2) and shuts off the discharge of air therefrom, characterized in that the double-acting shut-off device for the air pump (2) is a shut-off device which can be operated actively by  
25 the operating component (11), and in that the air piston is an air piston which can move freely at least over a short distance with respect to the operating component (11).
2. Device according to claim 1, characterized in that the double-acting shut-off device is designed in the form  
30 of a sealing ring (39) forming part of the operating component (11), and in that the piston of the air pump (2) is designed in the form of an annular piston (5), which is freely movable with respect to the other components, while the operating component (11) additionally comprises a  
35 driver (40), which is situated upstream of the sealing ring (39), viewed in the intended outflow direction of the air, in that an inner rim (8) of the annular piston (5) is

situated between the sealing ring (39) and the driver (40), and in that the driver (40), along its circumferential edge which can interact with the annular piston (5), comprises recesses, the sealing ring (39) and the driver (40) being  
5 able to interact with one another in a sealing manner in the at-rest position of the operating unit (1), and furthermore the distance between the sealing ring (5) and the driver (40) being larger, at the location of the inner rim (8) of the annular piston (5), than the thickness of  
10 the inner rim (8) of the annular piston (5), and in that it is possible to effect a connection to the outflow channel (15) between the sealing ring (39) and the driver (40).

3. Device according to claim 2, characterized in that the central opening in the freely movable annular piston  
15 (5) is as small as possible.

4. Device according to claim 2 or 3, characterized in that an additional driver (43) is present on the operating component (11) downstream of the sealing ring (39), viewed in the intended outflow direction.

20 5. Device according to claim 1, characterized in that the double-acting shut-off device is a component of the piston of the air pump (2), in that the piston of the air pump (2) is designed in the form of an annular piston (5), which is freely movable with respect to the other  
25 components, while the operating component (11) comprises two drivers (50, 51), between which the annular piston (5) is situated, the first driver (50), which is situated downstream of the annular piston (5), viewed in the intended outflow direction, having a larger radial  
30 dimension than the other, second driver (51), in that one or more air inlet openings (52) are present in the annular piston (5), which openings are situated between the outer circumference of the first and the second drivers (50, 51), viewed in the radial direction, and in that it is possible  
35 to make a connection to the outflow channel (15) between the drivers (50, 51).

6. Device according to claim 5, characterized in that the annular piston (5) comprises two axial, circumferential thickened portions (53, 54), which are located radially at




- a distance from one another and extend in opposite directions, a first thickened portion (53) which extends in the intended outflow direction and can interact with the first driver (50), and a second thickened portion (54) which extends in the opposite direction and can interact with the second driver (51), the first thickened portion (53) lying further towards the outside, in the radial direction, than the second (54).
7. Device according to one or more of the preceding claims, characterized in that the annular piston (5) is coupled locally (52) to the operating component so as to be movable.
8. Device according to one or more of the preceding claims, characterized in that a mixing chamber (35) is present for mixing air and liquid, which chamber is connected to the outflow channel (15), the discharge of the air pump and the discharge of the liquid pump.
9. Device according to one or more of the preceding claims, characterized in that one or more foam-forming components (37, 38) are present in the outflow channel.
10. Device according to one or more of the preceding claims, characterized in that the liquid piston (10) is a cylindrical component with an inlet side and a discharge side, which component is open on two sides and on the discharge side comprises a seat (19), with which a sealing element (20) extending into the liquid chamber (9) can interact, in that additionally that section of the sealing element (20) which extends into the chamber (9) can interact slidably with friction with an additional cylindrical component in the liquid piston chamber (9) in order to force the sealing element (20) into the seat (19) during filling of the piston chamber (9) and to force it out of the seat during emptying of the chamber (9).
11. Device according to one or more of Claims 1-10, characterized in that the shut-off device in the inlet of the liquid pump is designed in the form of a stopper (23), which can move freely between two stops (25, 26) in the liquid piston chamber (9) and can interact with a seat (45) in the liquid inlet, which stopper (23) moreover forms the


additional cylindrical component.


12. Operating unit evidently intended to be used in a device according to one or more of the preceding claims 1-11.

5 13. Piston intended for an air pump for an operating unit according to Claim 12.




2 / 5






4 / 5



5 / 5

*Fig. 5*

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/NL 96/00378

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 B05B11/00 B05B7/00

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 B05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	EP 0 736 462 A (YOSHINO KOGYOSHO CO LTD) 9 October 1996 see column 28, line 31 - column 29, line 40; figures 1-4 see column 26, line 45 - column 27, line 56	1-13
A	--- EP 0 613 728 A (DAIWA CAN COMPANY) 7 September 1994 cited in the application see the whole document	1
A	--- EP 0 544 549 A (L'OREAL) 2 June 1993 -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

18 December 1996

Date of mailing of the international search report

23.12.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Brévier, F



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/NL 96/00378

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0736462	09-10-96	JP-A- 8230924	10-09-96
		JP-A- 8268459	15-10-96
		AU-A- 3881495	17-06-96
		CA-A- 2180859	30-05-96
		WO-A- 9615952	30-05-96
		JP-A- 8230919	10-09-96
		JP-A- 8230961	10-09-96
-----			
EP-A-613728	07-09-94	AU-A- 5644294	15-09-94
		CA-A- 2117054	06-09-94
-----			
EP-A-544549	02-06-93	FR-A- 2684081	28-05-93
		DE-D- 69209788	15-05-96
		DE-T- 69209788	05-12-96
		ES-T- 2085594	01-06-96
-----			